



US009410252B2

(12) **United States Patent**
Okamura et al.

(10) **Patent No.:** **US 9,410,252 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **CORROSION INHIBITOR INJECTING METHOD**

(75) Inventors: **Masato Okamura**, Yokohama (JP); **Tetsuo Oosato**, Tokyo (JP); **Kazuo Murakami**, Kawasaki (JP); **Seiji Yamamoto**, Tokyo (JP); **Hiroyuki Arai**, Kamakura (JP); **Hidehiro Urata**, Yokohama (JP); **Hajime Hirasawa**, Yokohama (JP); **Osamu Shibasaki**, Yokohama (JP); **Koji Negishi**, Yokohama (JP)

(73) Assignee: **KABUSHIKI KAISHA TOSHIBA**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 179 days.

(21) Appl. No.: **14/345,148**

(22) PCT Filed: **Sep. 13, 2012**

(86) PCT No.: **PCT/JP2012/073503**

§ 371 (c)(1),
(2), (4) Date: **Mar. 18, 2014**

(87) PCT Pub. No.: **WO2013/039163**

PCT Pub. Date: **Mar. 21, 2013**

(65) **Prior Publication Data**

US 2014/0242299 A1 Aug. 28, 2014

(30) **Foreign Application Priority Data**

Sep. 15, 2011 (JP) 2011-202239

(51) **Int. Cl.**

C23F 11/18 (2006.01)

C23F 11/08 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **C23F 11/08** (2013.01); **C23F 11/18** (2013.01); **C23F 11/185** (2013.01); **C23F 15/00** (2013.01); **G21C 17/0225** (2013.01); **G21D 3/08** (2013.01); **Y02E 30/40** (2013.01)

(58) **Field of Classification Search**

CPC **C23F 11/00**; **C23F 11/08**; **C23F 11/18**; **C23F 11/185**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,940,939 B1 * 9/2005 Ichikawa G21C 17/022
376/301

2003/0180180 A1 9/2003 Okamura et al.

(Continued)

FOREIGN PATENT DOCUMENTS

AU 2010211602 A1 8/2011
JP 2001-276628 10/2001

(Continued)

OTHER PUBLICATIONS

Extended Search Report issued Apr. 1, 2015 in European Patent Application No. 12831961.3.

International Search Report Issued Nov. 6, 2012 in PCT/JP12/073503 Filed Sep. 13, 2012.

Primary Examiner — Elizabeth Burkhart

(74) Attorney, Agent, or Firm — Oblon, McClelland, Maier & Neustadt, L.L.P.

(57) **ABSTRACT**

A method for injecting a corrosion inhibitor injecting an oxidant and an anticorrosive agent-pH adjusting agent complex including an anticorrosive agent and a pH adjusting agent adsorbed on a surface of the anticorrosive agent into high temperature water in contact with a surface of a metal structural material and irradiating the high temperature water with a radioactive ray or an ultraviolet ray, wherein the anticorrosive agent of the anticorrosive agent-pH adjusting agent complex has, on the surface of the anticorrosive agent, an active site where the pH adjusting agent reacts with the oxidant, and the pH adjusting agent present on the surface of the anticorrosive agent of the anticorrosive agent-pH adjusting agent complex and/or in the high temperature water is oxidized with the oxidant by the irradiation with the radioactive ray or the ultraviolet ray to change pH adjusting ability of the pH adjusting agent and shift a pH of the high temperature water to a neutral side, and thereby deposition of the anticorrosive agent 11 to the metal structural material 65 is accelerated.

18 Claims, 10 Drawing Sheets

